



4x4



2012 MXU 450i

The new **MXU 450i** presents big time 4X4 utility machine performance in a mid-sized ATV. The powerful SOHC 443cc liquid-cooled EFI engine fires to life at the push of a button with all the power and punch to tackle the most rugged trails and get you through the tightest corners. KYMCO's automatic CVT transmission with low, high, neutral and reverse gears is easy to operate and puts instant power and torque to the maintenance free sealed shaft final drive. Shift on a fly 2WD to 4WD traction helps conquer even the most extreme off-road conditions while our class leading independent front and rear suspension smooth out the ride. On the job site or riding the weekend trails, this MXU 450i is packed with all the features you demand and at exceptional value.



Additional Features: Digital instrument cluster with gear indicator, 40kg front rack capacity and 80kg rear rack capacity, dual wishbone front and rear suspension, DOT approved headlight with high and low beam and rear brake light, shift on the fly 2WD/4WD, drilled front and rear rotors, 2 inch trailer hitch receiver.

Available Accessories:

Warn Winch RT25 with optional wireless control Wireless Brake Light

Engine type	Oil cooled, Single cylinder, 4 valve, 4 stroke
Displacement	442.9 cc
Bore & stroke	81x 71.2mm
Compression ratio	9.1:1
Valve train	S.O.H.C., chain drive
Fuel delivery	Electronic Fuel Injection
Transmission	Automatic CVT with High, Low, Neutral and Reverse
Front suspension	Dual A-Arm
Rear suspension	Dual A-Arm
Tires	25/8R12 front 25/10R12 rear
Brakes Front	Dual Disk / Single Piston Caliper
Rear	Single Disk/Single Piston Caliper
Seat height	843mm
Wheel base	1217 mm
Fuel capacity	15 litres
Dry weight	276 kg
Towing Capacity	1050 lbs
Available Colors:	









All KYMCO ATVs come with a 1 year limited warranty!



2011 MXU 450i

Engine Type	Liquid cooled, Single cylinder, 4 stroke
Displacement	442.9 cc
Bore & stroke	89 x 71.2 mm
Compression ratio	9.1: 1
Valve train	S.O.H.C., Chain Drive, 4 valve
Fuel Delivery	Electronic Fuel Injection
Ignition	Electronic Fuel Injection
Transmission	Automatic CVT
Transfer Gearshift Pattern	L/H/N/R/P
Spark plug	NGK CR7E
Emission	CEPA Environmental Registered with spark arrestor
Fuel tank capacity	15 litres
Tires	25/8-12 front; 25/10-12 rear
Front Suspension	Dual A-Arm
Rear Suspension	Dual A-Arm
Front Brakes	Dual Disk / Single piston calliper
Rear Brakes	Single Disk / Single piston calliper
Type Speedometer	Digital
Complete Size (L x W x H)	2108 x 1102 x 1192 mm
Seat Height	843 mm
Dry weight	275 kg
Towing Capacity	476 kg
Maximum Number of passengers	1
Warranty	One year limited warranty

